

PCT

WORLD INTELLECTUAL PROP.
International B

INTERNATIONAL APPLICATION PUBLISHED UNDER



(51) International Patent Classification 6 :

B65G 47/19, G01N 35/02

A1

(11) Li

WO 9608433A1

(43) International Publication Date: 21 March 1996 (21.03.96)

(21) International Application Number: PCT/FI94/00406

(22) International Filing Date: 15 September 1994 (15.09.94)

(71) Applicant (for all designated States except US): CLIDS OY
(FI/FI); Savilahdentie 6, FIN-70210 Kuopio (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): RIEKKINEN, Martti
(FI/FI); Naavakuusentie 3, FIN-90240 Oulu (FI).(74) Agent: PITKÄNEN, Hannu; Savilahdentie 6A, FIN-70210
Kuopio (FI).(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH,
CN, CZ, DE, DK, EE, ES, GB, GE, HU, JP, KE, KG, KP,
KR, KZ, LK, LT, LU, LV, MD, MG, MN, MW, NL, NO,
NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US,
UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF,
BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG),
ARIPO patent (KE, MW, SD).

Published


With international search report.

In English translation (filed in Finnish).

(54) Title: METHOD FOR MARKING OF A VESSEL AND A HANDLING DEVICE FOR APPLYING OF THE METHOD

(57) Abstract

The object of the invention is a method for marking a container (2) for the identification of the samples which it contains, in which method the container (2) is placed in a holder (1) and the holder (1) includes a memory unit (5) into which the machine readable identification data for the identification of the container (2) in the holder (1) is stored. In addition, the object of the invention is an equipment for the application of the method. In order to improve the processing of the sample in the method according to the invention the identification data stored in the memory unit (5) is read by the reading device of the handling equipment (14) and by the instruments of the handling equipment the sample is processed in a predetermined way and the data concerning the processing is transferred into the memory unit. The handling equipment relating to the invention consists of a reading device for reading the identification data and the instruments for processing the sample.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

METHOD FOR MARKING OF A VESSEL AND A HANDLING DEVICE FOR
APPLYING OF THE METHOD

5 The object of the invention is a method to mark a container
for the identification of the samples it contains, in which
method the container is mounted in a holder, which has a
memory unit for the storing of the machine readable identi-
fication data of the container in the holder. In addition,
10 the object of the invention is the handling equipment for
the application of the method, as defined in the introducti-
on part of the first device claim.

The present known method for marking the samples is that bar
code labels are glued to a test tube containing, for instan-
15 ce, blood samples. This label is printed by a printer when
the person who took the sample types the identification code
of the patient e.g., his name, into the patient data system.

The basic blood sample is transferred to the hospital labo-
20 ratory where it is identified on the basis of the label
glued to the test tube. After the patient who gave the
sample is recognized by the bar code, the laboratory person-
nel is able to find out which tests should be done to the
blood sample, on the basis of the record they have access
25 to. On the basis of this, the basic blood sample is divided
into partial samples by pipeting or by an automatic divider.
A label is glued to the test tube of every partial sample
and the necessary information needed for the identification
of a patient is marked on the label either in plain text or
30 by bar code.

The partial blood samples are brought to analyzers for the
necessary tests. The results of these tests and the informa-
tion on the labels are registered and forwarded to the
35 doctor attending the patient.

The greatest drawback of the above mentioned known method is

that the samples or the results of the samples may be mixed by human error making, naturally, the test results of the blood samples of the patients unreliable. This kind of an error may happen, for instance, in the process of dividing the basic blood samples into partial samples in case the person doing the dividing accidentally glues a wrong label to a wrong test tube or in the registering of the results of the analysis. Also, there may be problems in the dividing of the sample into partial samples and/or in their handling. One particular problem is the inconvenience of handling the labels. The labels may come off or they are fastened so tight that their removal in the cleaning is difficult.

The purpose of this invention is to solve the above mentioned problems and to offer for use a very reliable and simple method and a handling equipment by which test tubes can be marked for identification, identified and handled so that there is no need for separate code labels and no risk of mixing the samples of different patients. In addition, the purpose of the invention is to introduce a method and a handling equipment by which the sample can be handled fast, reliably and in a predetermined way and by which all the necessary data to process the sample is following with the sample.

These goals are met by the method relating to the invention and by the handling equipment, which are characteristic of the claim 1 and of the first claim for equipment.

The invention is based on the idea that the identification data stored in the memory unit is read by the reading device of the handling equipment and the sample is handled, in a predetermined way, by the handling equipment instruments and the data necessary for the handling is transferred to the memory unit. The sample is identified positively and reliably by the handling equipment. Furthermore, the sample can be handled in a desired way, fast and securely, after the

identification and the data needed for the processing and/or identification of the sample can be stored in the memory unit of the basic sample container or in the memory unit of further sample containers.

5

The method is extremely usable for the handling of the blood samples of the patients in a hospital. The container, in this application, refers to a test tube or equivalent usable for the handling of blood samples, urine samples etc. The
10 handling refers to the procedures done to the sample in the container. This kind of a procedure is for example the dividing of the basic blood sample into partial samples for processing in various analyzers.

15 In the preferred application of the invention an inductively readable memory is used as a memory unit. Data, which is machine readable, can be stored in the memory unit, without having to turn the test tube to a certain position. Thus, all the data pertaining to the sample will be stored in the
20 memory unit immediately after taking the sample. The advantage of this is also that the memory unit is reusable unlike the known bar code labels and it can be used repeatedly or even washed.

25 According to the method all the data necessary for the handling of the sample is stored in the memory unit of the holder. In practice, this is not possible when using bar code labels because the data that can be included in one bar code label is very limited. Because all the data necessary
30 for the handling of the sample is readable from the memory of the holder, from where it can be transferred to the memory unit of the holder of the partial sample containers in the process of dividing the basic sample, the persons handling the sample do not need to use other information
35 sources while handling the sample. The use of labels and equivalent marking devices is no more necessary. The marking of partial samples is easier because the handling equipment

used in this method is a dividing device, because the dividing device automatically transfers the identification data from the memory unit of the holder of the basic blood sample into the memory unit of the holder of the respective partial blood sample. The most remarkable advantages of the method related to the invention are the minimizing of the chances of human error, the possibility of having simple and reliable information about what has to be done to the sample for example into how many partial samples it has to be divided and the possibility to find fast and simply, without the need of labels or equivalent devices, a specific sample among other similar ones just by reading the identification data in the memory unit of the holder.

In addition, the object of the invention is the handling equipment of the sample, characterized in that the handling equipment consists of a reading device for reading the identification data stored in the memory unit of the holder and of the instruments to handle the sample, identified by the identification data of the container, in a predetermined way. The most significant advantage of the handling equipment is that it automatically performs the predetermined measures to the sample like, for instance, divides it into partial samples after the handling equipment has identified the sample by the identification data stored in the memory unit of the holder. Thus, for instance, such a situation is avoided that a person handling a certain sample by mistake performs measures intended for another sample. Still, if he for instance does not divide the sample into sufficient number of portions, it is possible that there are not enough partial samples for all the analyzers needing partial samples.

In a preferred embodiment of the handling equipment according to the invention, the handling device is a dividing device for dividing the basic blood sample into partial samples, which dividing device is equipped with instruments

to store the identification data it reads from the memory unit of the basic sample into the memory unit of each partial sample holder. Besides being simple, the most significant advantage of this method is the fact that the chance of human error is completely eliminated in the process of marking the sample for identification.

In the following, the invention is explained in greater detail with reference to the attached drawings, in which Figure 1 shows a holder employed in the method, Figure 2 shows a data terminal employed in the method of the invention, and Figure 3 shows a preferred application of the equipment related to the method of the invention.

Figure 1 shows the side view and partial cross-section of a holder 1. As illustrated in Fig. 1 a container 2, suitable for handling a blood sample or any other equivalent sample, is placed in a plastic holder 1. The container is a test tube which is properly closed by a plug 3. Both the holder 1 and the container 2 are of long cylindrical shape and round when viewed from above.

The diameter of the vertical cavity, open at the top, of the holder 1 is a bit smaller than the outside diameter of the holder 2. The walls of the holder 1 flex out by the pressure applied to them by the insertion of the container 2 into the vertical cavity of the holder. This flex-out is further helped by the vertical slot on the wall of the holder, which slot has the shape of the letter "U" as seen in Fig. 1. Besides helping the flex-out of the holder and the fastening of the container 2 into the holder 1, the slot makes it possible to see the filled amount inside the transparent container 2 even though the container is placed in the holder 1. The amount of fill may be estimated, depending on the situation, either by viewing or by automatic devices.

There is a cylindrical cavity underneath the bottom level of the vertical cavity of the holder 1. The memory unit 5 is attached into this cavity. The memory unit consists of a memory circuit, a sender, a receiver and a coil. The memory unit 5 is an inductively readable memory device the principle of which is described, for instance, in the FI-patent publication 85 079. Both the holder 1 and its memory unit are washable. The capacity of the memory circuit of the memory unit 5 is so designed that it can store the data of the patient who has given the blood sample in the container 2 and the data for the handling procedures of the blood sample in the container. Here the handling procedures refer to the analyses which have to be done to the blood sample. So the data in the memory circuits of the memory unit 5 is informative, for instance, as to who is the donor of the blood sample and the number of the analyses, in other words, into how many portions the blood sample in the container 2 has to be divided. All the data in the memory circuit is inductively readable which means that the data can be read without having to set the read head of the reading device in physical contact with the holder 1. There is no need to turn the holder into a certain position in relation to the read head, but the data can be read from the memory circuit just by bringing the memory circuit close to the read head of the reading device.

The bottom face of the holder 1 and the attached memory are perpendicular to the vertical centerline of the holder 1 and of the container 2, so the holder 1 stays in an upright position, as shown in Fig. 1, when it is put for instance on a table. Because of the holder 1, even the test tube 2 with a spherical bottom stays upright when placed in the holder 1.

Figure 2 shows a portable data terminal 7, employed in a preferred application of the method of the invention. This data terminal can write and read data into and from the

memory unit attached to the holder 1 in Fig. 1. The handheld terminal consists of the display 9 and the keyboard 11. To read or write data the holder 1 is brought close to the writing/reading head 8 of the terminal 7. Thus the data transfer between the memory unit of the holder and the terminal 7 is inductively performed. The advantageous wireless data transfer between the terminal 7 and the data system of the hospital enables the storing of the identification data for instance the names of those patients, who need to give a blood sample, into the terminal 7. After the blood sample is taken, the name of the patient is fed into the handheld terminal 7 through the keyboard and simultaneously the holder and the container holding the blood sample are brought close to the reading head of the handheld terminal. The data of the handling procedures of the blood sample is inductively transferred into the memory unit of the holder 1.

Figure 3 shows a preferred embodiment of the equipment according to the invention. The blood samples of the patients and the tests to be done to the blood samples of each patient are fed into the hospital data system 12. Into the data system is also fed the data of all the analyzers 13 in the hospital, so the system is capable of deciding which analyzer or analyzers will perform the tests to the blood sample. The portable terminal 7 and the hospital data system have an advantageous wireless connection. This way the data of necessary blood samples can be transferred to the terminal 7. Accordingly, the nurse taking blood samples of the patients will have the information about who is to give a blood sample.

The blood sample is put in a container for example in the test tube 2 as shown in Fig. 1 and the test tube is placed in the holder 1 as shown in Fig. 1. The container holding the blood sample and the holder are brought close to the writing/reading head of the terminal 7 and by typing a code

through the terminal keyboard the patient, who gave the sample, is identified. After the identification of the patient the data of the patient and the data concerning the tests that have to be done to the blood sample are transferred by the terminal to the memory unit attached to the holder 1.

After the blood samples have been taken, the containers holding the blood samples are transferred to the dividing device 14. The dividing device has a reading head for reading the data from the memory unit attached to the bottom of the holder 1. The reading head inductively reads the data from the memory unit. This data tells the following; who is the patient who gave the blood sample, into how many partial samples the blood sample in the container is to be divided and by which analyzers the tests to the blood sample are to be performed. On the basis of this information the blood sample in the container is divided into partial samples by the dividing device, and the partial samples are placed in containers to be transferred to various analyzers. The container, in which the basic blood sample has been, is transferred away from the dividing device to be washed and reused. The containers, into which the partial samples are placed, have memory units too and therefore while filling the partial sample containers, the dividing device inductively writes the identification data of the partial sample into the holder of each partial sample.

The filled containers of the partial samples are transferred to the analyzers 13, which perform the necessary analyses. During the process of analyzing the identification data of the patient is read from the holder of each respective partial sample for example the name of the patient. This particular identification data and the results of the performed analysis are fed into the hospital data system 12, where the doctor attending the patient can read it. In Fig. 3 the arrows starting from the right side of the analyzers

13 represent the data flow from the analyzers 13 into the hospital data system 12.

5 In another embodiment according to the invention only the data needed to identify the patient is stored in the memory of the holder 1 by the handheld terminal 7. In this particular application the dividing device 14 and the analyzers 13 are directly connected to the hospital data system 12 enabling them to receive other necessary information directly
10 from the data system after the holder 1 has been identified by the identification data stored in its memory. For example, the dividing device 14 receives the information, concerning into how many portions the basic blood sample has to be divided, directly from the hospital data system 12. This
15 is made possible by the identification data stored in the memory of the holder 1. Accordingly, the memory of the holder 1 can be minimized.

20 The above description and the related drawings must not be understood to limit the applications of the invention, but strictly illustrative. It shall be noticed that regardless of what has been said earlier about utilizing the invention in the handling of a blood sample, the invention can be utilized as well in the handling of any other sample like,
25 for instance, in the handling of animal urine sample. Also, the reading and the writing of the memory do not necessarily need to be inductive, but any other similar technique can be applied. The method of the invention and the handling equipment can be varied within the scope of the annexed claims.

CLAIMS

1. A method for marking a container (2) for identification, in which method the container (2) is placed in a holder (1),
5 and the holder (1) includes a memory unit (5) into which machine readable identification data of the container (2) in the holder (1) is stored, c h a r a c t e r i z e d in that the identification data stored in the memory unit (5) is read by the reading device of the handling equipment (14)
10 and by the instruments of the handling equipment the sample is processed in a predetermined way and the information related to the process is transferred to the memory unit.
2. A method as defined in claim 1, c h a r a c t e r i -
15 z e d in that the memory unit (5) used in the method is an inductively readable memory consisting of a memory circuit, a sender, a receiver and a coil.
3. A method as defined in claim 1 or claim 2, c h a r a c -
20 t e r i z e d in that during the handling process the partial samples are placed by the handling equipment (14) in containers (2), to the holders (1) of which the memory unit (5) is attached and that the identification data read from the memory (5) of the holder (1) of the basic sample is
25 stored by the handling equipment (14) into the memory unit (5) attached to the holder (1) during the dividing.
4. A method as defined in claim 3, c h a r a c t e r i -
z e d in that the sample in the container (2) is a blood
30 sample, the blood sample in the container (2) is divided into partial samples by the dividing equipment, and that the dividing equipment (14) reads from the memory unit (5) of the holder (1) of the basic sample the number of the necessary partial samples.
- 35 5. A handling equipment for processing the sample in the container in a predetermined way, the container (2) being

placed in the holder (1) and to the holder (1) a memory unit (5) being attached for the storing of identification data, c h a r a c t e r i z e d in that the handling equipment (14) consists of a reading device for reading the identification data stored in the memory unit (5) and the instruments for processing the sample in the container (2) identified by the identification data in a predetermined way and for transferring the data related to the processing into the memory unit.

10

6. A handling equipment as defined in claim 5, c h a r a c t e r i z e d in that the handling equipment (14) is a dividing device, by which the basic sample is divided into partial samples on the basis of the information included in the identification data of the sample and concerning the handling of the sample.

15

7. A method as defined in claim 5 or claim 6, c h a r a c t e r i z e d in that the memory unit (5) is an inductively readable memory consisting of a memory circuit, a sender, a receiver and a coil.

20

8. A handling equipment as defined in claims 5 - 7, c h a r a c t e r i z e d in that the sample mentioned is a blood sample.

25

1/2




FIG. 1




FIG. 2

2/2




FIG. 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 94/00406

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B65G 47/19, G01N 35/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B65G, G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DX,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 3526125 (S.R. GILFORD ET AL), 1 Sept 1970 (01.09.70), column 5, line 5 - line 8, figure 7, claim 1 --	1,5,8
A	EP, A2, 0243915 (ITOH, TERUAKI), 4 November 1987 (04.11.87), page 9, line 17 - line 23, figures 1,2 --	1-8
A	US, A, 3660638 (RUDOLF OBERLI), 2 May 1972 (02.05.72), claim 1 --	1-8
A	EP, A2, 0351988 (QUATRO BIOSYSTEMS LIMITED), 24 January 1990 (24.01.90), claims 1,2 --	1-8

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

A document member of the same patent family

Date of the actual completion of the international search

19 April 1995

Date of mailing of the international search report

09-05-1995

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Bengt Christensson
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 94/00406

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP, A1, 0039145 (LABSYSTEMS OY), 4 November 1981 (04.11.81), claim 1 -- -----	1-8

INTERNATIONAL SEARCH REPORT

Information on patent family members

25/02/95

International application No.

PCT/FI 94/00406

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US-A-	3526125	01/09/70	CH-A-	508876	15/06/71
			DE-A,B,C	1815864	21/08/69
			FR-A-	1596170	15/06/70
			GB-A-	1264964	23/02/72
			GB-A-	1264965	23/02/72
			NL-A-	6818264	23/06/69
EP-A2-	0243915	04/11/87	SE-T3-	0243915	
			DK-B-	169428	31/10/94
			EP-A,B-	0264456	27/04/88
			SE-T3-	0264456	
			FI-B,C-	92765	15/09/94
			GB-A,B-	2189884	04/11/87
			GB-A,B-	2197645	25/05/88
			JP-C-	1860329	27/07/94
			JP-A-	62221525	29/09/87
			US-A-	4798095	17/01/89
			US-A-	4982553	08/01/91
			WO-A-	8706709	05/11/87
			JP-C-	1860942	27/07/94
			JP-A-	62223413	01/10/87
			JP-A-	62222706	30/09/87
			JP-A-	62221845	29/09/87
			JP-A-	62222182	30/09/87
US-A-	3660638	02/05/72	CH-A-	513393	30/09/71
			DE-A-	2041660	11/03/71
			FR-A-	2059352	28/05/71
			GB-A-	1326249	08/08/73
			SE-B,C-	379427	06/10/75
EP-A2-	0351988	24/01/90	DE-D,T-	68908807	03/02/94
			ES-T-	2043022	16/12/93
			JP-A-	2067962	07/03/90
			US-A-	5122342	16/06/92
EP-A1-	0039145	04/11/81	SE-T3-	0039145	
			AT-E,T-	10549	15/12/84
			JP-A-	56162036	12/12/81
			SU-A-	1163807	23/06/85
			US-A-	4431924	14/02/84